

TECHNICAL CHARACTERISTICS

PURLINE organic flooring | wineo 1200 to glue

Permanently elastic polyurethane flooring according to EN 16776
Without the addition of chlorin, without plasticisers or solvents.

wineo

	wineo 1200 wood XL V4	wineo 1200 stone XL
Format	1500 x 250 mm	1000 x 500 mm
Product thickness	2.2 mm	2.2 mm
Weight	3 kg/m ²	3 kg/m ²
Planks / m² per box	14 / 5.25 m ²	12 / 6.00 m ²
Boxes / m² per pallet	56 / 294.00 m ²	50 / 300.00 m ²
Guarantee	30 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de	



Classification		Product composition
Utilization class 23 EN ISO 10874	Domestic area with intensive usage	1 Top element • PU-top layer with surface structure • decor paper • stabilisation
Utilization class 33 EN ISO 10874	Commercial sector with heavy usage	
Utilization class 42 EN ISO 10874	Light industry sector with moderate usage	
Scratch resistance EN 16776, annex A	Utilization class 33 ≥ 6 N Utilization class 42 ≥ 7 N	2 Base layer ecuran high performance composite
R9 Anti slip category DIN 51130	R 9	3 Backing Integrated Fleece TEC-System
Staining and chemical resistance EN ISO 26987	Very good resistance according to the concentration and residence time	wood XL V4 joint lacquered
Light fastness EN ISO 105-B02	~ 7	
Residual indentation EN ISO 24343-1	≤ 0.10 mm	
Effect of a furniture leg EN 424	Foot type 2 – no visible change	
Castor chair test EN ISO 4918	25000 revolutions no damage with rolls type W	
Thermal resistance ISO 8302	0.01 (m ² K)/W	
Impact sound reduction EN ISO 10140	in test	
Dimension stability EN ISO 23999	≤ 0.15 %	
Flexural behaviour EN ISO 24344	≥ 20 mm	
REACH	free from SVHC substances ≥ 0.1 %	
Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203	

CE Windmüller GmbH
Nord-West-Ring 21
D-32832 Augustdorf

DOP: 2001010
EN 14041:2004 / AC2006
1658

www.wineo.de

ÉMISSIONS DANS L'AIR INTÉRIEUR

A+

A+ A B C

Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

THIRD-PARTY VERIFIED

EPD

Institut Bauen und Umwelt e.V.

DGNB
NAVIGATOR

Registrierungs-Code
NAPCCU

www.dgnb-navigator.de

UL GREENGUARD

GREENGUARD GOLD

Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.