














TECHNICAL CHARACTERISTICS

wineo 800

Heterogeneous resilient-flooring for glueless installation - Covering type according to EN ISO 10582

wineo

	wineo 800 wood	wineo 800 wood XL	wineo 800 stone XL	
Format	1212 x 185 mm	1505 x 237 mm	914 x 480 mm	
Product thickness	5 mm	5 mm	5 mm	
Planks, tiles / m² per box	8 / 1.79 m ²	6 / 2.14 m ²	6 / 2.63 m ²	
Boxes / m² per pallet	64 / 114.56 m ²	56 / 119.84 m ²	44 / 115.72 m ²	
Guarantee Extended warranty	25 years for private use according to Windmüller warranty conditions - www.wineo.de + 5 years for laying on PU underlay mat			




Classification			Product composition	
	Utilization class 23 EN ISO 10874	Domestic area with intensive usage	1	Surface seal
	Utilization class 33 EN ISO 10874	Commercial sector with heavy usage	2	Surface texture Various embossings
	Wear layer binder content EN ISO 10582	Typ I	3	Wear layer Thickness 0.55 mm
	R10 Anti slip category DIN 51130	R 10	4	Design Decor film
	Staining and chemical resistance EN ISO 26987	Good resistance according to the concentration and residence time	5	Base layer with glass fibre reinforced
	Light fastness EN ISO 105-B02	Light fastness (procedure 2) ≥ 6	6	Profile connection Connect Technology 
	Residual indentation EN ISO 24343-1	≤ 0.1 mm	7	Backing
	Castor chair test ISO 4918	25000 revolutions no damage with rolls type W		Underlay material silentCOMFORT (available separately)
	Thermal resistance EN 12667	≤ 0.021 (m ² K)/W without underlay mat ≤ 0.031 (m ² K)/W with silentCOMFORT		stone - real joint selected decors
	silent COMFORT Impact sound reduction EN ISO 16251-1	~ 7 dB ~ 16 dB with silentCOMFORT		
	Dimensional stability EN ISO 23999	~ 0.1 %		
	REACH	free from SVHC substances ≥ 0.1 %		
	Disposal	<u>Private:</u> Possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203		



CE - 18 -


Windmüller GmbH
Nord-West-Ring 21
D-32832 Augustdorf

DOP: 0301010
EN 14041:2004 / AC2006
1658

www.wineo.de

ÉMISSIONS DANS L'AIR INTÉRIEUR

 **A+**

A+ A B C

Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)

Phthalat frei  **factory made coated**

Relevant information:

- R 10 Decor „Heavy Metal“ excluded.
- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.
- Cleaning and care: see separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.